

## METHODOLOGY FOR APPLICATION OF MYK ASOLIN WS

### Description:

**MYK ASOLIN WS** is a ready to use solvent based, high penetration colorless siloxane based water repellent.

**Packing:** 5, 20, and 200 Kg pack

### Methodology for Application:

#### **Step-1:- Application of MYK ASOLIN WS**

Pre-moistened the surface before doing the application.

### Application of MYK ASOLIN WS:

**MYK Asolin WS** can be applied by brush or spray on the well prepared surface.

### Application Areas:

**MYK Asolin WS** is recommended for moisture protection of facades or for inclined area, excellent for porous concrete, brick, lime sand stone, concrete cement bonded artificial stone etc.

**Excellent:** for porous concrete, bricks, lime sand stone, mineralic paint

**Good:** Concrete cement bonded artificial stone, asbestos cement

**Different:** Natural Stone

**Limited Suitability:** plastic Resin plaster

**Not Suitable:** Gypsum, plastic resin paints

### Coverage:

100-1000 ml / m<sup>2</sup>

### Protection:

**MYK ASOLIN WS** should be applied with gloves and care should be taken to see that it doesn't fall on screen or eyes. Splashes on the eyes have to be immediately washed with plenty of water and medical advice to be taken.

**Note:** - All coverages mentioned above are theoretical and under laboratory conditions, MYK Schomburg strongly recommends site trials to ascertain actual coverages.